

552,565

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
4 November 2004 (04.11.2004)


PCT

(10) International Publication Number  
**WO 2004/093589 A1**

- (51) International Patent Classification<sup>7</sup>: A43C 1/00, 7/00, A43B 5/00
- (21) International Application Number: PCT/EP2004/001684
- (22) International Filing Date: 20 February 2004 (20.02.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
PD2003A000083 24 April 2003 (24.04.2003) IT
- (71) Applicant (for all designated States except US): TECNICA S.P.A. [IT/IT]; Via Fante d'Italia, 56, I-31040 Giavera del Montello (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PELLEGRINI, Alfred [IT/IT]; Via delle Ginestre, 50, I-31044 Montebelluna (IT).
- (74) Agents: FABRIS, Stefano et al.; Cantaluppi & Partners S.r.l., Via Matteotti, 26, I-35137 Padova (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: FOOTWEAR WITH A LACE FASTENING



(57) Abstract: Footwear (1) with a lace fastening comprises an opening (5) with a first edge (5a) and a second edge (5b) which are juxtaposed and each of which carries a respective plurality of lacing eyes, and at least two laces (20, 21) extending through respective pairs of the lacing eyes (11a,b - 17a,b). The ends of both of the laces converge on both of the edges of the opening, with at least one end of each lace (20, 21) extending through a respective end lacing eye (17a, 17b) of the fastening provided on each of the opposite edges.

WO 2004/093589 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

**Declarations under Rule 4.17:**

- *as to the identity of the inventor (Rule 4.17(i)) for the following designation US*
- *of inventorship (Rule 4.17(iv)) for US only*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*